



EKINOPS PM_LC4-MP2-A

200G Line Module for ETS Compact Chassis

DATA SHEET 05 | 2024

KEY FEATURES & BENEFITS

- 200G OTN switching and transport capacity in a single-slot
- Multi-rate support from 10Gbps to 200Gbps
- Transparent multi-protocol client support
- Pluggable dual function interfaces—tributary or line
- Tunable DWDM or gray optics
- Embedded management & timing functions
- Standard G.709 mapping & FEC

APPLICATIONS

- 10G service aggregation over OTN networks
- Multiprotocol service delivery
- Edge OTN switching and WDM transport
- Network demarcation and interconnection

OVERVIEW

EKINOPS PM_LC4-MP2-A is a multi-rate, multi-protocol service aggregation module for the Ekinops Transport Switch Compact Chassis (ETSc) product family. It consists of SFP+, QSFP28 and CFP2 pluggable interfaces with 200Gbps of total line card capacity. As a single-slot, pluggable module for the ETS Compact Chassis platform, the PM_LC4-MP2-A provides support for a wide range of service types and speeds. Because it is fully compatible with the centralized switch fabric, and PM_LC5-MP4-D (500G Line Card), it provides multiple switching options depending on the chassis configuration and functional requirements. It can either interface directly with the centralized switch fabric to create a full, non-blocking configuration, or directly with other modules for through-backplane switching between line card pairs. It can also be used in cross-ponder mode in which ODUk frames are switched locally with all traffic remaining on the card. The cross-ponder configuration is ideal for cost-effectively extending OTN switching and aggregation functions to the network edge for seamless connectivity to the network core.

The PM_LC4-MP2-A provides switching capability from ODU0 to ODU4 including ODU2 and ODU2e meaning any service, regardless of protocol or speed, can be managed individually across any OTN-based network, and even across multiple network boundaries.

The PM_LC4-MP2-A operates as a 200G total capacity tributary aggregating, grooming and switching client Ethernet 10GbE and OTN services OTU2/2e. For OTN-based services in tributary mode, the PM_LC4-MP2-A provides two-stage OTN multiplexing, and in line module mode it provides single stage OTN multiplexing.

In tributary mode, ten SFP+ interfaces can support 10GbE services in addition to OTU2 and OTU2e. The dual QSFP28 ports support 100 GbE or OTU4 and the dual CFP2 interfaces can support either 100/200G OTU4.

APPLICATIONS

The PM_LC4-MP2-A is designed for efficient aggregation, grooming and switching of 10G services and above at medium to large sites on the network. The PM_LC4-MP2-A can also be used for mobile fronthaul applications to deliver 10G to 200G links between antenna sites and node sites to both aggregate small-cells and provide the capacity required as the mobile network migrates from 4G to 5G. Its coherent transport capabilities support 5G network slicing with the low latency connectivity that the various network functions require to maintain performance.




Figure 1: PM_LC4-MP2-A Interfaces



EKINOPS PM_LC4-MP2-A

200G Line Module for ETS Compact Chassis

MANAGEMENT

Ekinops Celestis NMS provides standards-based Telecommunications Network Management (TMN) management functions for the OTN Switch Equipment, Networks and Services. Celestis NMS has a distributed architecture in order to ensure flexibility for managing a variety of network technologies, high availability, high performance and scalability. Celestis NMS applications can be installed in a single standalone server for managing small networks or in multi-server clusters to ensure high availability and scalability when managing large networks.

SDN-ready, Celestis NMS, connects to the PM_LC4-MP2-A via NETCONF while the northbound interface (NBI) is based on REST/JSON and SNMP

SPECIFICATIONS

OPTICAL INTERFACES

Type	No. Ports	Tributary	OTN Line
SFP+	20	10GbE	OTU2/OTU2e; DWDM or B&W
QSFP28	2	100GbE	OTU4; B&W
CFP2	2		OTU4/OTUC2; DWDM or B&W

MANAGEMENT

Protocol	NETCONF (YANG model); SNMP
Remote management	GCC

PHYSICAL SPECIFICATIONS

Module size	1 slot in ETSc2 and ETSc6
Power consumption (typical)	125W
Power consumption (max.)	130W
Operating temperature	0°C to +50°C / +32°F to +122°F
Storage temperature	-20°C to +85°C / -4°F to +185°F

ORDERING INFORMATION

PLUGGABLE MODULE (PM)

PRODUCT CODE	DESCRIPTION
PM_LC4-MP2-A	Line Card 200G, 2xCFP2 100G/200G interfaces + 2xQSFP28 100G B/W interfaces + 20xSFP+ 10G interfaces. Total 200G for OTN or 200G for multiprotocol ports. OTU4 coherent CFP2 WDM interfaces, tunable for 80 Ch ITU-T G.657.1. Client interface 10GbE, 100GbE, OTU2/2e and OTU4

EKINOPS CHASSIS

PRODUCT CODE	DESCRIPTION
RM_ETSc2	3RU empty chassis OTN Switching
RM_ETSc6	6RU empty chassis OTN Switching

CONTACT



www.ekinops.com

Ekinops EMEA
sales.eu@ekinops.com

Ekinops APAC
sales.asia@ekinops.com

Ekinops Americas
sales.us@ekinops.com